

531567

Rec'd PCT/PTO 14 APR 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/035435 A1

(51) International Patent Classification: B65G 53/22,
B65D 88/28

(21) International Application Number:
PCT/EP2003/050722

(22) International Filing Date: 16 October 2003 (16.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02079300.6 16 October 2002 (16.10.2002) EP

(71) Applicant (for AE, AG, AL, AM, AT, AU, AZ, BA, BB, BE, BG, BR, BY, BZ, CH, CN, CO, CR, CU, CY, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, FR, GB, GD, GE, GH, GM, GR, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,

SC, SD, SE, SG, SK, SL, SY, SZ, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW only): SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).

(71) Applicant (for CA only): SHELL CANADA LIMITED [CA/CA]; 400 - 4th Avenue S.W., Calgary, T2P 2H5 (CA).


(72) Inventor; and

(75) Inventor/Applicant (for US only): BERGGREN, Wouter Detlof [NL/NL]; Badhuisweg 3, NL-1031 CM Amsterdam (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: VESSEL FOR STORING PARTICULATE MATTER AND DISCHARGE DEVICE FOR USE IN THE SAME



(57) Abstract: The invention pertains to a vessel (1) for storing particulate matter, such as pulverised coal or fly ash, comprising a main part (2) and, at its bottom portion, at least one discharge device (3), which comprises a converging outer shell (10) and a permeable, converging inner shell (14) positioned in the outer shell (10), the discharge device (3) being connected to the main part (2) by means of a first flange (9) at or near the lower rim of the bottom portion of the main part (2) and a second flange (11) at or near the upper rim of the outer shell (10). The inner shell (14) is secured to the inner wall of the outer shell (10) of the discharge device (3), preferably to the inner wall of the second flange (11). Thus, the number of gaskets is reduced and/or the positioning of the inner shell becomes less critical.

WO 2004/035435 A1